

MATERIAL SAFETY DATA SHEET

prepared 01/24/03

SPRED DURA LATEX PORCH & FLOOR

ICI Paints North America

925 Euclid Avenue, Cleveland, Ohio 44115

EMERGENCY TELEPHONE NO. (800) 545-2643

38XX

HAZARDS IDENTIFICATION (ANSI Section 3)

Primary route(s) of exposure : Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure :

Inhalation : Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, drowsiness, dizziness and/or lightheadedness, headache, coughing, central nervous system depression, difficulty of breathing, severe lung irritation or damage, kidney damage.

Skin contact : Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting. Possible sensitization to skin.

Eye contact : Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, tearing of eyes, redness of eyes.

Ingestion : Ingestion may cause mouth and throat irritation, dizziness and/or lightheadedness, headache, nausea, vomiting, gastro-intestinal disturbances, severe abdominal pain, abdominal pain, apathy, central nervous system depression, respiratory problems, intoxication, kidney damage, pulmonary edema, loss of consciousness, acute poisoning, respiratory failure, cardiac failure, brain damage.

Medical conditions aggravated by exposure : Eye, skin, respiratory disorders asthma-like conditions kidney disorders respiratory disorders

FIRST-AID MEASURES (ANSI Section 4)

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.

Skin contact : Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use.

Eye contact : Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion : If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES (ANSI Section 5)

Fire extinguishing media : Dry chemical or foam water fog. Carbon dioxide. Closed containers may burst if exposed to extreme heat or fire. In closed tanks, water or foam may cause frothing or eruption.

Fire fighting procedures : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus. Self-contained breathing apparatus recommended.

Hazardous decomposition or combustion products : Carbon monoxide, carbon dioxide, acrid fumes, toxic gases. Acrylic monomers oxides of calcium

ACCIDENTAL RELEASE MEASURES (ANSI Section 6)

Steps to be taken in case material is released or spilled : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Evacuate all unnecessary personnel. Place collected material in proper container. Small spills - use absorbent to pick up residue and dispose of properly.

HANDLING AND STORAGE (ANSI Section 7)

Handling and storage : Store below 100°F (38°C). Keep away from heat, sparks and open flame. Keep from freezing.

The information contained herein is based on data available at the time of preparation of this data sheet which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and the users of this material.

Complies with OSHA hazard communication standard 29CFR1910.1200.

Other precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sandling) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection.

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection : Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian z94.4) Approved elastomeric sealing-surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/tam) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian z94.4).

Ventilation : Provide dilution ventilation or local exhaust to prevent build-up of vapors.

Personal protective equipment : Eye wash, safety shower, safety glasses or goggles, Impervious gloves, impervious clothing.

STABILITY AND REACTIVITY (ANSI Section 10)

Under normal conditions : Stable see section 5 fire fighting measures

Materials to avoid : Oxidizers, acids, reducing agents, halogens.

Conditions to avoid : Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame.

Hazardous polymerization : Will not occur

TOXICOLOGICAL INFORMATION (ANSI Section 11)

Supplemental health information : No additional effects are anticipated

Carcinogenicity : Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silicon is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen. The international agency for research on cancer (IARC) has classified carbon black as possibly carcinogenic to humans (group 2b) based on insufficient evidence in animals and inadequate evidence in humans.

Reproductive effects : No reproductive effects are anticipated

Mutagenicity : No mutagenic effects are anticipated

Teratogenicity : Some laboratory test results have shown ethylene glycol to be an animal teratogen.

ECOLOGICAL INFORMATION (ANSI Section 12)

No ecological testing has been done by ICI paints on this product as a whole.

DISPOSAL CONSIDERATIONS (ANSI Section 13)

Waste disposal : Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

REGULATORY INFORMATION (ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard

criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

Physical Data

(ANSI Sections 1, 9, and 14)

Product Code	Description	Wt. / Gal.	VOC gr./ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
3800	spred floor acrylic latex enamel - white	10.75	88.80	60.43	none	212-401	*210	paint ** protect from freezing **
3801	spred floor acrylic latex enamel - chateau gray	10.20	88.80	62.06	none	212-401	*210	paint ** protect from freezing **
3804	spred floor acrylic latex enamel - rich brown	10.10	88.92	62.35	none	212-401	*210	paint ** protect from freezing **
3806	spred floor acrylic latex enamel - harbor gray	10.21	88.92	61.95	none	212-401	*210	paint ** protect from freezing **
3808	spred floor acrylic latex enamel - lime green	10.03	88.80	62.34	none	212-401	*210	paint ** protect from freezing **
3810	spred floor acrylic latex enamel - tlc red	10.47	88.80	62.33	none	212-401	*210	paint ** protect from freezing **
3825	spred floor acrylic latex enamel - white	10.79	88.88	60.27	none	212-401	*210	paint ** protect from freezing **
3887	spred floor acrylic latex enamel - intermedlite tint base	10.34	88.80	62.06	none	212-401	*210	paint ** protect from freezing **
3890	spred floor acrylic latex enamel - accent li ht base	9.86	88.68	63.38	none	212-401	*210	paint ** protect from freezing **

Ingredients

Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	3800	3801	3804	3806	3808	3810	3825	3887	3890
1,2-ethanediol	ethylene glycol	107-21-1	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5
limestone	limestone	1317-85-3	1-5	5-10	1-5	5-10	5-10	5-10	1-5	1-5	5-10
iron oxide	iron oxide	1332-37-2			1-5						
carbon black	carbon black	1333-86-4			.1-1.0	.1-1.0					
titanium dioxide	titanium dioxide	13463-67-7	10-20		1-5		1-5		10-20	5-10	
quartz	quartz	14808-60-7			.1-1.0		.1-1.0				
aluminum hydroxide	aluminum hydroxide	21645-61-2	1-5								1-5
propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	texanol	25265-77-4	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5	1-5
nepheline syenite	feldspar-type minerals	37244-96-5	10-20	5-10	10-20	5-10	10-20	5-10	10-20	10-20	10-20
c.i. pigment yellow 42	yellow iron oxide	51274-00-1			1-5		1-5				
silica	amorphous silica	7631-86-9	1-5						1-5	1-5	
water	water	7732-18-5	40-50	40-50	40-50	40-50	40-50	40-50	40-50	40-50	50-60
acrylic resin	acrylic resin	Sup. Conf.	20-30	20-30	20-30	20-30	20-30	20-30	20-30	20-30	20-30

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV			OSHA-PEL			S.R. Std.	S2	S3	CC	H	M	N	I	O
		8-Hour TWA	STEL	C	8-Hour TWA	STEL	C									
ethylene glycol	107-21-1	not est.	not est.	100 mg/m3	not est.	not est.	not est.	not est.	n	y	y	n	n	n	n	n
limestone	1317-85-3	10 mg/m3	not est.	not est.	not est.	not est.	5 mg/m3	not est.	n	n	n	n	n	n	n	n
iron oxide	1332-37-2	5 mg/m3	not est.	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
carbon black	1333-86-4	3.5 mg/m3	not est.	not est.	not est.	not est.	3.5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	y
titanium dioxide	13463-67-7	10 mg/m3	not est.	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
quartz	14808-60-7	.05 mg/m3	not est.	not est.	not est.	not est.	.01 mg/m3	not est.	not est.	not est.	not est.	n	n	n	y	n
aluminum hydroxide	21645-61-2	10 mg/m3	not est.	not est.	not est.	not est.	5 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	a
texanol	25265-77-4	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	j
feldspar-type minerals	37244-96-5	5 mg/m3	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
yellow iron oxide	51274-00-1	5 mg/m3	not est.	not est.	not est.	not est.	10 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n
amorphous silica	7631-86-9	10 mg/m3	not est.	not est.	not est.	not est.	6 mg/m3	not est.	not est.	not est.	not est.	n	n	n	n	n

FacNotes:
C=Ceiling - Concentration that should not be exceeded.
S=Skin - Additional exposure, over and above airborn exposure, may result from skin absorption.

n/a=not applicable
not est.=not established
CC=CERCLA Chemical
Sup. Conf.=Supplier Confidential

ppm=parts per million
mg/m3=milligrams per cubic meter
Sup. Conf.=Supplier Confidential

S2=Sara Section 202 EHS
S3=Sara Section 313 Chemical
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant
P=Pollutant, S=Severe Pollutant
Carcinogenicity Listed By:
N=NTP, I=IARC, O=OSHA, y=yes, n=no